Column & Fire Equipment Guidelines		Booth 3334
General booth guidelines can be found he	ow/important-guidelines/display-guidelines-rules-reg	
5'-2" 5'-2" F 3'-3" F S S	E FE 3'-11" E20' 3'-8" 2'-5"	S 2(
	3334	3434
REFERENCE GUIDELINES (unless otherise noted <u>FS (Fire Strobe)</u> : Located at 20' height; Hall E are 1 are 6'7" height from the floor. <u>FE (Fire Extinguisher)</u> : Must remain visible, access <u>SP (Fire Speaker)</u> : 6"x6" & located at 9'9" height fro and unobstructed <u>FHC (Fire Hose Connection)</u> : Must remain visible, a Door Release): Must not be blocked	12' height from the floor; ACC lobbies ible and unobstructed om the floor and shall be visible	Building Support Column Exhibitors are free to brand & build around columns, as long as fire equipment is clear and nothing is adhered to the column or physical building.
 measurements. This may vary slightly onsite (All fire equipment on columns must remain visi clear to the aisle. Fire alarm devices have a strobe and a speake 	ble and accessible at all times and fire hoses must be	

FREEMAN

EVERY EFFORT HAS BEEN MADE TO ENSURE THE ACCUPACY OF ALL INFORMATION CONTAINED ON THIS FLOORPLAN. HOWEVER, NO WARRANTES, EITHER EXPRESSED OF IMPLIED, ARE MADE WITH RESPECT TO THIS FLOORPLAN. IF THE LOCATION OF BUILDING COLUMNS, UTILIES OR OTHER ARCHITECTURAL COMPONENTS OF THE FACILITY IS A CONSIDERATION IN THE CONSTRUCTION OR USAGE OF AN EXHIBIT, IT IS THE SOLE RESPONSIBILITY OF THE EXHIBITOR TO PHYSICALLY INSPECT THE FACILITY TO VERIFY ALL DIMENSION AND LOCATIONS. ©COPYRIGHT 2007, FREEMAN, ALL RIGHTS RESERVED.